

MATERIAL SAFETY DATA SHEET

B-Cap 50 Antimicrobial Agent



MSDS Ref. No.: 7722-84-1-7

Date Approved: 04/30/2006

Revision No.: 9

This document has been prepared to meet the requirements of the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200; the Canada's Workplace Hazardous Materials Information System (WHMIS) and, the EC Directive, 2001/58/EC.

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: B-Cap 50 Antimicrobial Agent

SYNONYMS: Hydrogen Peroxide Solutions 40 to 60%

GENERAL USE: B-Cap 50 Antimicrobial Agent is used for biofouling control in cooling and process water systems, as a paper mill biocide, and for general slime control.

B-Cap 50 is used in any FIFRA regulated formulation requiring H₂O₂ as the active ingredient.

MANUFACTURER

FMC CORPORATION
FMC Peroxygens
1735 Market Street
Philadelphia, PA 19103
(215) 299-6000 (General Information)

FMC of Canada Ltd.
FMC Peroxygens
PG Pulp Mill Road
Prince George, BC V2N2S6
(250) 561-4200 (General Information)

EMERGENCY TELEPHONE NUMBERS

(281) 474-8750 (Plant: Pasadena, TX, US - Call Collect)
(250) 561-4221 (Plant: Prince George, BC, Canada - Call Collect)
(303) 595-9048 (Medical - U.S. - Call Collect)

For leak, fire, spill, or accident emergencies, call:
(800) 424-9300 (CHEMTREC - U.S.A.)
(613) 996-6666 (CANUTEC - Canada)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

- Clear, colorless, odorless liquid
- Oxidizer.
- Contact with combustibles may cause fire.
- Decomposes yielding oxygen that supports combustion of organic matters and can cause overpressure if confined.

- Corrosive to eyes, nose, throat, lungs and gastrointestinal tract.

POTENTIAL HEALTH EFFECTS: Corrosive to eyes, skin, nose, throat and lungs. May cause irreversible tissue damage to the eyes including blindness.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Wt.%	EC No.	EC Class
Hydrogen Peroxide	7722-84-1	40 - 60	231-765-0	C; R20/22-34, O; R8
Water	7732-18-5	40 - 60	231-791-2	Not classified

4. FIRST AID MEASURES

EYES: Immediately flush with water for at least 15 minutes, lifting the upper and lower eyelids intermittently. See a medical doctor or ophthalmologist immediately.

SKIN: Immediately flush with plenty of water while removing contaminated clothing and/or shoes, and thoroughly wash with soap and water. See a medical doctor immediately.

INGESTION: Rinse mouth with water. Dilute by giving 1 or 2 glasses of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. See a medical doctor immediately.

INHALATION: Remove to fresh air. If breathing difficulty or discomfort occurs and persists, contact a medical doctor.

NOTES TO MEDICAL DOCTOR: Hydrogen peroxide at these concentrations is a strong oxidant. Direct contact with the eye is likely to cause corneal damage especially if not washed immediately. Careful ophthalmologic evaluation is recommended and the possibility of local corticosteroid therapy should be considered. Because of the likelihood of corrosive effects on the gastrointestinal tract after ingestion, and the unlikelihood of systemic effects, attempts at evacuating the stomach via emesis induction or gastric lavage should be avoided. There is a remote possibility, however, that a nasogastric or orogastric tube may be required for the reduction of severe distension due to gas formation.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Flood with water.

FIRE / EXPLOSION HAZARDS: Product is non-combustible. On decomposition releases oxygen which may intensify fire.

FIRE FIGHTING PROCEDURES: Any tank or container surrounded by fire should be flooded with water for cooling. Wear full protective clothing and self-contained breathing apparatus.

FLAMMABLE LIMITS: Non-combustible

SENSITIVITY TO IMPACT: No data available

SENSITIVITY TO STATIC DISCHARGE: No data available

6. ACCIDENTAL RELEASE MEASURES

RELEASE NOTES: Dilute with a large volume of water and hold in a pond or diked area until hydrogen peroxide decomposes. Hydrogen peroxide may be decomposed by adding sodium metabisulfite or sodium sulfite after diluting to about 5%. Dispose according to methods outlined for waste disposal.

Combustible materials exposed to hydrogen peroxide should be immediately submerged in or rinsed with large amounts of water to ensure that all hydrogen peroxide is removed. Residual hydrogen peroxide that is allowed to dry (upon evaporation hydrogen peroxide can concentrate) on organic materials such as paper, fabrics, cotton, leather, wood or other combustibles can cause the material to ignite and result in a fire.

7. HANDLING AND STORAGE

HANDLING: Wear chemical splash-type monogoggles and full-face shield, impervious clothing, such as rubber, PVC, etc., and rubber or neoprene gloves and shoes. Avoid cotton, wool and leather. Avoid excessive heat and contamination. Contamination may cause decomposition and generation of oxygen gas which could result in high pressures and possible container rupture. Hydrogen peroxide should be stored only in vented containers and transferred only in a prescribed manner (see FMC Technical Bulletins). Never return unused hydrogen peroxide to original container, empty drums should be triple rinsed with water before discarding. Utensils used for handling hydrogen peroxide should only be made of glass, stainless steel, aluminum or plastic.

STORAGE: Store drums in cool areas out of direct sunlight and away from combustibles. For bulk storage refer to FMC Technical Bulletins.

COMMENTS: VENTILATION: Provide mechanical general and/or local exhaust ventilation to prevent release of vapor or mist into the work environment.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS

Chemical Name	ACGIH	OSHA	Supplier
Hydrogen Peroxide	1 ppm (TWA)	1 ppm (PEL)	

ENGINEERING CONTROLS: Ventilation should be provided to minimize the release of hydrogen peroxide vapors and mists into the work environment. Spills should be minimized or confined immediately to prevent release into the work area. Remove contaminated clothing immediately and wash before reuse.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical splash-type monogoggles and a full-face shield made of polycarbonate, acetate, polycarbonate/acetate, PETG or thermoplastic.

RESPIRATORY: If concentrations in excess of 10 ppm are expected, use NIOSH/DHHS approved self-contained breathing apparatus (SCBA), or other approved atmospheric-supplied respirator (ASR) equipment (e.g., a full-face airline respirator (ALR)). DO NOT use any form of air-purifying respirator (APR) or filtering facepiece (AKA dust mask), especially those containing oxidizable sorbants such as activated carbon.

PROTECTIVE CLOTHING: For body protection wear impervious clothing such as an approved splash protective suit made of SBR Rubber, PVC (PVC Outershell w/Polyester Substrate), Gore-Tex (Polyester trilaminate w/Gore-Tex), or a specialized HAZMAT Splash or Protective Suite (Level A, B, or C). For foot protection, wear approved boots made of NBR, PVC, Polyurethane, or neoprene. Overboots made of Latex or PVC, as well as firefighter boots or specialized HAZMAT boots are also permitted. DO NOT wear any form of boot or overboots made of nylon or nylon blends. DO NOT use cotton, wool or leather, as these materials react RAPIDLY with higher concentrations of hydrogen peroxide. Completely submerge hydrogen peroxide contaminated clothing or other materials in water prior to drying. Residual hydrogen peroxide, if allowed to dry on materials such as paper, fabrics, cotton, leather, wood or other combustibles can cause the material to ignite and result in a fire.

GLOVES: For hand protection, wear approved gloves made of nitrile, PVC, or neoprene. DO NOT use cotton, wool or leather for these materials react RAPIDLY with higher concentrations of hydrogen peroxide. Thoroughly rinse the outside of gloves with water prior to removal. Inspect regularly for leaks.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR:	Odorless
APPEARANCE:	Clear, colorless liquid
AUTOIGNITION TEMPERATURE:	Non-combustible

BOILING POINT:	110°C (229°F) (40%); 114°C (237°F) (50%)
COEFFICIENT OF OIL / WATER:	Not available
DENSITY / WEIGHT PER VOLUME:	Not available
EVAPORATION RATE:	>1 (Butyl Acetate = 1)
FLASH POINT:	Non-combustible
FREEZING POINT:	-41.4°C (-42.5°F) (40%); -52°C (-62°F) (50%)
ODOR THRESHOLD:	Not available
OXIDIZING PROPERTIES:	Strong oxidizer
PERCENT VOLATILE:	100%
pH:	(as is) 1.0 to 3.0
SOLUBILITY IN WATER:	(in H ₂ O % by wt) 100%
SPECIFIC GRAVITY:	(H ₂ O = 1) 1.15 @ 20°C/4°C (40%); 1.19 @ 20°C/4°C (50%)
VAPOR DENSITY:	(Air = 1): Not available
VAPOR PRESSURE:	22 mmHg @ 30°C (40%); 18.3 mmHg @ 30°C (50%)

COMMENTS:

pH (1% solution) : 5.0 - 6.0

10. STABILITY AND REACTIVITY

CONDITIONS TO AVOID:	Excessive heat or contamination could cause product to become unstable.
STABILITY:	Stable (heat and contamination could cause decomposition)
POLYMERIZATION:	Will not occur
INCOMPATIBLE MATERIALS:	Reducing agents, wood, paper and other combustibles, iron and other heavy metals, copper alloys and caustic.
HAZARDOUS DECOMPOSITION PRODUCTS:	Oxygen which supports combustion.
COMMENTS:	Materials to Avoid : Dirt, organics, cyanides and combustibles such as wood, paper, oils, etc.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS: 70% hydrogen peroxide: Severe irritant (corrosive) (rabbit) [FMC Study Number: ICG/T-79.027]

SKIN EFFECTS: 50% hydrogen peroxide: Severe irritant (corrosive) (rabbit) [FMC Study Number: I89-1079]

DERMAL LD₅₀: 70% hydrogen peroxide: > 6.5 g/kg (rabbit) [FMC Study Number: ICG/T-79.027]

ORAL LD₅₀: 50% hydrogen peroxide: > 225 mg/kg (rat) [FMC Study Number: I86-914]

INHALATION LC₅₀: 50% hydrogen peroxide: > 0.17 mg/l (rat) [FMC Study Number: I89-1080]

TARGET ORGANS: Eye, skin, nose, throat, lungs

ACUTE EFFECTS FROM OVEREXPOSURE: Severe irritant/corrosive to eyes, skin and gastrointestinal tract. May cause irreversible tissue damage to the eyes including blindness. Inhalation of mist or vapors may be severely irritating to nose, throat and lungs.

CHRONIC EFFECTS FROM OVEREXPOSURE: The International Agency for Research on Cancer (IARC) has concluded that there is inadequate evidence for carcinogenicity of hydrogen peroxide in humans, but limited evidence in experimental animals (Group 3 - not classifiable as to its carcinogenicity to humans). The American Conference of Governmental Industrial Hygienists (ACGIH) has concluded that hydrogen peroxide is a 'Confirmed Animal Carcinogen with Unknown Relevance to Humans' (A3).

CARCINOGENICITY:

Chemical Name	IARC	NTP	OSHA	Other
Hydrogen Peroxide	Not listed	Not listed	Not listed	(ACGIH) Listed (A3, Animal Carcinogen)

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Channel catfish 96-hour LC₅₀ = 37.4 mg/L
 Fathead minnow 96-hour LC₅₀ = 16.4 mg/L
 Daphnia magna 24-hour EC₅₀ = 7.7 mg/L
 Daphnia pulex 48-hour LC₅₀ = 2.4 mg/L
 Freshwater snail 96-hour LC₅₀ = 17.7 mg/L

For more information refer to ECETOC "Joint Assessment of Commodity Chemicals No. 22, Hydrogen Peroxide." ISSN-0773-6339, January 1993

CHEMICAL FATE INFORMATION: Hydrogen peroxide in the aquatic environment is subject to various reduction or oxidation processes and decomposes into water and oxygen. Hydrogen

peroxide half-life in freshwater ranged from 8 hours to 20 days, in air from 10-20 hrs. and in soils from minutes to hours depending upon microbiological activity and metal contaminants.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: An acceptable method of disposal is to dilute with a large amount of water and allow the hydrogen peroxide to decompose followed by discharge into a suitable treatment system in accordance with all regulatory agencies. The appropriate regulatory agencies should be contacted prior to disposal.

14. TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION (DOT)

PROPER SHIPPING NAME:	Hydrogen peroxide, aqueous solutions with more than 40% but not more than 60% hydrogen peroxide.
PRIMARY HAZARD CLASS / DIVISION:	5.1 (Oxidizer)
UN/NA NUMBER:	UN 2014
PACKING GROUP:	II
LABEL(S):	Oxidizer, Corrosive
PLACARD(S):	5.1 (Oxidizer)
ADDITIONAL INFORMATION:	DOT Marking: Hydrogen Peroxide, aqueous solution with more than 40%, but not more than 60% Hydrogen Peroxide, UN 2014 Hazardous Substance/RQ: Not applicable 49 STCC Number: 4918775 DOT Spec: stainless steel/high purity aluminum cargo tanks and rail cars. UN Spec: HDPE drums. Contact FMC for specific details.

INTERNATIONAL MARITIME DANGEROUS GOODS (IMDG)

PROPER SHIPPING NAME:	Hydrogen peroxide, aqueous solutions with not less than 20%, but not more than 60% hydrogen peroxide.
------------------------------	---

INTERNATIONAL CIVIL AVIATION ORGANIZATION (ICAO) / INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA)

PROPER SHIPPING NAME:

Hydrogen peroxide (40 - 60%) is forbidden on Passenger and Cargo Aircraft, as well as Cargo Only Aircraft.

OTHER INFORMATION:

Protect from physical damage. Keep drums in upright position. Drums should not be stacked in transit. Do not store drum on wooden pallets.

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355, APPENDIX A):

Hydrogen Peroxide > 52%, RQ: 1000 lbs. Planning Threshold: 10,000 lbs.

SECTION 311 HAZARD CATEGORIES (40 CFR 370):

Fire Hazard, Immediate (Acute) Health Hazard

SECTION 312 THRESHOLD PLANNING QUANTITY (40 CFR 370):

The Threshold Planning Quantity (TPQ) for this product, if treated as a mixture, is 10,000 lbs; however, this product contains the following ingredients with a TPQ of less than 10,000 lbs.:
None, (conc. <52%), (hydrogen peroxide, 1000 lbs. when conc is >52%)

SECTION 313 REPORTABLE INGREDIENTS (40 CFR 372):

Not listed

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT)

CERCLA DESIGNATION & REPORTABLE QUANTITIES (RQ) (40 CFR 302.4):

Unlisted (Hydrogen Peroxide); RQ = 100 lbs.; Ignitability, Corrosivity

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA INVENTORY STATUS (40 CFR 710):

Listed

RESOURCE CONSERVATION AND RECOVERY ACT (RCRA)

RCRA IDENTIFICATION OF HAZARDOUS WASTE (40 CFR 261):

Waste Number: D001, D002

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):

Product Identification Number: 2014
Hazard Classification / Division: Class C (Oxidizer), Class D, Div. 2, Subdiv. B (Toxic), Class E (Corrosive)
Ingredient Disclosure List: Listed

INTERNATIONAL LISTINGS

Hydrogen peroxide:
China: Listed
Japan (ENCS): (1)-419
Korea: KE-20204
Philippines (PICCS): Listed

HAZARD, RISK AND SAFETY PHRASE DESCRIPTIONS:

Hydrogen Peroxide, (Index #008-003-00-9):

EC Symbols:	C	(Corrosive)
	O	(Oxidizer)
EC Risk Phrases:	R20/22	(Harmful by inhalation and if swallowed.)
	R34	(Causes burns)
	R8	(Contact with combustible material may cause fire)
EC Safety Phrases:	S1/2	(Keep locked up and out of reach of children.)
	S3	(Keep in a cool place.)
	S17	(Keep away from combustible material.)
	S26	(In case of contact with eyes, rinse immediately with plenty of water and seek medical advice)
	S28	(After contact with skin, wash immediately with plenty of water and soap.)
	S36/37/39	(Wear suitable protective clothing, gloves and eye/face protection.)
	S45	(In case of accident or if you feel unwell, seek medical advice immediately - show the label where possible.)

16. OTHER INFORMATION

HMIS

Health	3
Flammability	0
Physical Hazard	1
Personal Protection (PPE)	H

Protection = H (Safety goggles, gloves, apron, the use of a supplied air or SCBA respirator is required in lieu of a vapor cartridge respirator)

HMIS = Hazardous Materials Identification System

Degree of Hazard Code:

4 = Severe
 3 = Serious
 2 = Moderate
 1 = Slight
 0 = Minimal

NFPA

Health	3
Flammability	0
Reactivity	1
Special	OX

SPECIAL = OX (Oxidizer)

NFPA = National Fire Protection Association

Degree of Hazard Code:

4 = Extreme
 3 = High
 2 = Moderate
 1 = Slight
 0 = Insignificant

REVISION SUMMARY:

This MSDS replaces Revision #8, dated April 04, 2005.

Changes in information are as follows:

Section 1 (Product and Company Identification)

Section 16 (Other Information)

FMC Logo - FMC Corporation Trademark

© 2006 FMC Corporation. All Rights Reserved.

NOTE: NFPA Reactivity is 3 - when greater than 52%

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable where such product is used in combination with any other materials or in any process. Use of this product is regulated by the U.S. Environmental Protection Agency (EPA). It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Further, since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.